



## Hot water high pressure washers

# PW-H40 PW-H40/4



### Standard accessories



### Optional accessories



## Features

- Electric motor, 4-pole, 1400 rpm, continuous duty with double bearing and thermal cutout. Extends the working life of mechanical components
- Pressure adjustment and steam knob incorporated in the pump
- Crankshaft pump with brass head and ceramic pistons
- Control panel with: motor and burner start-up, temperature regulation, detergent tap, professional gauge to display working pressure at all times
- Antiscale device with pump controlled by electronic card. The quantity product can be regulated according to water hardness
- The four large diameter front wheels make the machine more stable and easier to transport
- The wheels are fixed to a steel frame
- The detergent and fuel tanks hold 20 litres and are incorporated in the trolley. With caps for emptying and cleaning
- Ergonomic handle for easy convenient transport, complete with lance holder



Easy handling on every kind of surface (cement, dirt, tracks, gravel, etc.).



Wheel brake to stabilise the machine on all surface.



Machine designed for raising.



Code	Model	Remote control	Pressure (bar)	Flow rate (l/h)	Voltage (Ph-V-Hz)	Absorbed power (kW)	Motor (HP)	RPM	Detergent tank (l)	Weight (kg)	Dimensions (cm)
IDAC40329	PW-H40/4 D1813P T	Total Stop D	40÷175	400÷800	3-400-50	5.5	6	1400	20	109	105x75x90
IDAC40356	PW-H40 D1915 T	Total Stop D	40÷190	450÷900	3-400-50	5.5	6	1400	20	125.2	105x75x90
IDAC40357	PW-H40 D2017P T	Total Stop ITS	40÷200	500÷1000	3-400-50	7.2	7.5	1400	20	143.4	105x75x90

In all models, the output water temperature is 30÷140°C.